

DOPPIE™ ComPact Printer

(Direct On Plastic Printer with Imaging Electronics)



The DOPPIE ComPact printer delivers a simple, low-maintenance solution for ID cards without compromising on quality. Small and robust, designed to be portable, the Compact is ideal to take on-site to events and perfect for situations where space is limited.

Summary of Printer Features:

- Extremely compact and lightweight
- Single side printing
- Full colour edge to edge printing
- 300 dpi dye-sublimation printing technology
- Industry leading 24-bit continuous tone printing
- 144 cards per hour*
- First ever rotating, simple to read and use 2-line LCD display panel to fit any office environment
- Optional front or back card exit – ideal if space is tight
- Easy to change all-in-one ribbon cassette
- Low maintenance
- 16Mb Image Memory
- Windows compatibility
- USB 2.0 output



www.identilam.com



Identilam plc John Bostock House Faygate Horsham
 Sussex RH12 4DN England t: 44 (0) 1293 851711
 f: 44 (0) 1293 851742 sales@identilam.co.uk



SPECIFICATIONS:

Printing system	Single-sided 300dpi, 24-bit continuous tone printing, 16.7million colors
Printing method	Thermal transfer dye-sublimation
Print media	PVC or polyester cards with polished PVC finish
Media size	CR-80: 85.6 x 54mm
Media thickness	.76mm
Print area	Single-sided edge to edge
Input hopper	Removable 100 cards feeder
Output hopper	30 cards
Image memory	16Mb with parallel processing, four memory modes
System memory	2.25Mb
Display	Rotating LCD 16 character 2-line display shows printer status and diagnostic prompts
Print ribbon options:	YMCK 250 prints, K 1250 prints, & BK/OP 250 prints
Print speed*	(YMCKO) less than 144 cards per hour
Interface	USB 2.0
Dimensions	180mm (h) x 329mm (w) x 222mm (d)
Weight	6.5kg
Operating temperature	65 to 80°F / 10 to 35°C 35-85%RH/without condensing
Power source	AC Power source AC100/240v 50/60Hz auto-switching
Agency listing	UL: UL1950: UL1950-1993 CE Class B FCC A & B
Drivers	Windows compatible (inc Vista)
OPTIONS	Contactless smart card encoder

* Print speed indicates approximate batch print speed and is measured from the time a card feeds into the printer to the time it ejects from the printer. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is depend on the size of the file, the CPU, the amount of PC memory, and the amount of resources at the time of the print job.

Issued 19/11/09

www.identilam.com



Identilam plc John Bostock House Faygate Horsham
Sussex RH12 4DN England t: 44 (0) 1293 851711
f: 44 (0) 1293 851742 sales@identilam.co.uk